



EZ-Slick 600

General Application Instructions

Proper application is essential to maximize durability, shine, and performance. This guide will walk you through the step-by-step process to ensure a professional-grade result.

MADE IN USA

APPLICATION MATERIALS

- EZ-Slick 600 Coating
- Applicator pad
- Edgeless Microfiber towel
- Gloves (Recommended)

Surface Preparation:

Surfaces should be relatively clean. 600 can be used as a clean and coat application.

We recommend washing and drying the surface for best results.

APPLICATION

SURFACES ARE RELATIVELY CLEAN AND DRY

Product can be applied in direct sun if needed!

Product Preparation:

- Lightly shake the EZ-Slick 600 bottle to mix.

Non-porous Surface Application Process:

Use on : Paint - Gelcoat - Glass - Polished Metal - Smooth plastics - Electronic screens - and more

- Moisten the applicator with Ceramlock 600, including edges of the pad.
- With the pad flat on the surface, apply to the surface in a circular motion. Apply more product to pad every few feet of surface. The coating will have a wet white haze look while wiping the surface.
- Allow the coating to set up for **5-10 minutes** before wiping. The coating will turn into a white dust. The dust can be left on the surface indefinitely, as long as the minimum time to set up is reached. You could essentially wipe product on your whole car before wiping it off!
- **Buffing:** Use a new, high quality, edgeless microfiber towel to ensure no scratching when removing dried product. Gently wipe off excess coating to reveal a smooth, glossy finish.
- A second coating may be applied at any time, one coat is usually enough to seal the surface.

Note: Do not use product on porous plastic trim.

Curing and Finalizing:

- Coating is dry to touch in 1-2 hours.
- Avoid exposure to water for 2 days.
- Full cure in 5 days.

Aftercare:

Do not wax. Wash with Vehicle/Marine soap of your choice.

Use soft brushes and microfiber towels when washing. Dry with high quality towels or chamois (shammy).

For maximum longevity, wash your coated surface every 1-2 weeks and avoid automatic car washes.

SUPPORT

Contact us with any questions or concerns!

www.ceramlockcoatings.com

team@ceramlockcoatings.com

DISCLAIMER: Results may vary based on application methods, surface preparation, and environmental conditions. Refer to SDS for full handling and safety precautions. Ceramlock Coatings Inc, is not liable for misuse or unintended results. Test on a small area before full application.